

TITAN X4

Weather Protected Multi LED Batten

IP65 LED Batten Market Comparison

MEASURABLE	M-ELEC TITAN X4 ML-TN40X4-M	ATOM AT9877	ROBUS RSU4812CCT3-24	HANECO TRIPROOF40W12-TRI	CLIPSAL CLITPWPLED2	SAL SL9726/40TC	PIERLITE BWPECO454E4
IP Rating	65	65	65	65	65	65	65
600mm and 1200mm version available							
Emergency model							
Emergency model compliant with AS2293		NA	NA	NA	NA		NA
Sensor model							
Green model (eyewash station)*							
Yellow model (anti-insect)*							
Combined sensor & emergency model							
IK rating	10	08	08	08	08	08	08
Suspension clips included		NA		NA	NA	NA	
Efficacy (lm/W)	100-126	100	86-109	101-110	95	85-92.5	100
Wattage (W)	38-41	48	47.6-50.7	40	40	40	45
Total lumen output (lm)	4000-5040	4860	4280-5120	4050-4410	3800	3400-3700	4500
Body colour	Grey	Grey	Grey	Grey	Grey	Grey	Grey
Cover clips	Stainless	NA	Stainless	Stainless	Stainless	Stainless	Stainless
Body material	Polycarbonate	NA	Polycarbonate	Polycarbonate	Polycarbonate	Polycarbonate	Polycarbonate
Back and end entry		NA	NA	NA	NA	NA	
Warranty period (Yrs)	5	3	5	5	NA	3 residential 5 commercial	3
Emergency battery warranty	1	NA	NA	1	NA	1	NA
CRI	80	80	80	80	80	80	80
Operating temperature (°C)	-20 to +50	-10 to +40	-25 to +40	-30 to +50	-10 to +50	-20 to +40	-10 to +40
Output colour (K)	3000K 4000K 6000K Selectable	4000K Only	3000K 4000K 6500K Selectable	4000K 5000K 6000K Selectable	5000K Only	3000K 4000K 6000K Selectable	4000K Only
Size (LxWxH)	1250 x 117 x 70mm	1200 x 100 x 68mm	1232 x 130 x 77mm	1215 x 116 x 75mm	1274 x 140 x 90mm	1251 x 118 x 77mm	1265 x 130 x 92mm

YES
 NO
 Information not available NA

PLEASE NOTE:

All data on this sheet is for comparison purposes only and has been sourced through online available information. M-Elec take no responsibility for the accuracy and if incorrect information is found we encourage you to advise us so we can update the chart.

*Available for projects only

